

PA

THIS INSTRUMENT PREPARED BY: (NAME) Brenda Broome, Residential Real Estate
Compass Bank
(ADDRESS) 15 South 20th Street, Suite 1502
Birmingham, Alabama 35233

STATE OF ALABAMA)
COUNTY OF SHELBY)

FULL SATISFACTION OF RECORDED LIEN

(COMPASS BANK, FORMERLY)

KNOW ALL MEN BY THESE PRESENTS, That, Central Bank of the South, a corporation,
acknowledges full payment of the indebtedness secured by that certain mortgage executed by CRESTWOOD HOMES, INC. on November 5, 1992,
which said mortgage was recorded in the office of the Judge of Probate Court of Shelby County,
Alabama, in Instrument Number ~~Book No.~~ 1992-26292, Page No. _____
(and assigned to _____ in _____ Book No. _____
Page No. _____), and does further hereby release and satisfy said mortgage.

SEE ATTACHED EXHIBIT A FOR LEGAL DESCRIPTION

Inst # 1994-16236

05/19/1994-16236
01:24 PM CERTIFIED

(COMPASS BANK, FORMERLY) JUDGE OF PROBATE
SHELBY COUNTY 11.00
002 HCD

In Witness Whereof, Central Bank of the South, a corporation, has caused these
presents to be executed this 17th day of May, 19 94.

(COMPASS BANK, FORMERLY)
Central Bank of the South
By [Signature]
Its: Vice President

STATE OF ALABAMA)
COUNTY OF JEFFERSON)

I, the undersigned Notary Public, in and for said County in said State, hereby certify that _____
Philip R. Webb whose name as Vice President of
(COMPASS BANK, FORMERLY)
Central Bank of the South, a corporation, is signed to the foregoing instrument, and who is
known to me, acknowledged before me on this day that, being informed of the contents of the instrument, he
as such officer and with full authority, executed the same voluntarily for and as the act of said corporation.
Given under my hand and Official seal this 17th day of May, 19 94.

[Signature]
Notary Public MY COMMISSION EXPIRES JUNE 12, 1994

EXHIBIT "A"

Part of the South one-half of the NW 1/4 of the NE 1/4 of Section 10, Township 21 South, Range 3 West, Shelby County, Alabama, being more particularly described as follows: Beginning at the NE corner of said one-half of the NW 1/4 of the NE 1/4 of said Section 10, run in a southerly direction along the East line of said South one-half of the NW 1/4 of the NE 1/4 for a distance of 667.65 feet to an existing iron pin, being the SE corner of said NW 1/4 of NE 1/4; thence turn an angle to the right of 125 deg. 13 min. 20 sec. and run in a northwesterly direction for a distance of 151.86 feet to an existing iron pin, being on a curve; said curve being concave in a northwesterly direction and having a central angle of 24 deg. 33 min. 54 sec. and a radius of 69.36 feet; thence turn an angle to the left (82 deg. 54 min. 48 sec. to the chord of said curve) and run in a southwesterly direction along the arc of said curve for a distance of 29.74 feet to an existing iron pin, being the point of ending of said curve; thence continue in a southwesterly direction along the line tangent to the end of said curve for a distance of 25.0 feet to an existing iron pin; thence turn an angle to the right of 90 deg. and run in a northwesterly direction for a distance of 104.01 feet to an existing iron pin, to the point of beginning of a new curve; said new curve being concave in a southerly direction and having a central angle of 71 deg. 42 min. 16 sec. and a radius of 25.0 feet; thence turn an angle to the left and run along the arc of said curve for a distance of 31.29 feet to an existing iron pin, being the point of beginning of another curve; said third curve being concave in a northwesterly direction and having a central angle of 6 deg. 12 min. 16 sec. and a radius of 266.30 feet; thence run in a southwesterly direction along the arc of said curve for a distance of 28.84 feet to an existing iron pin and being the point of ending of said third curve; thence run in a southwesterly direction along the line tangent to the end of said curve for a distance of 57.99 feet to an existing iron pin; thence turn an angle to the left of 78 deg. 43 min. 55 sec. and run in a southerly direction for a distance of 125.37 feet to an existing iron pin, being on the South line of said NW 1/4 of the NE 1/4 of Section 10; thence turn an angle to the right of 90 deg. and run in a westerly direction along the South line of said 1/4-1/4 Section for a distance of 892.15 feet to an existing iron pin, being on the East right-of-way line of Shelby County Highway #264; said point also being on a curve and said curve being concave in an easterly direction and having a central angle of 12 deg. 04 min. 48 sec. and a radius of 778.44 feet; thence turn an angle to the right and run in a northerly direction along the East right-of-way line of Shelby County Highway #264 and along said curved line for a distance of 164.12 feet to an existing iron pin, being the point of ending of said curve; thence continue in a northerly direction and along said East right-of-way line of Shelby County Highway #264 for a distance of 503.71 feet to an existing iron pin, being on the North line of said South one-half of the NW 1/4 of the NE 1/4 of said Section 10; thence turn an angle to the right of 91 deg. 37 min. 27 sec. and run in an easterly direction along the North line of said South one-half of the NW 1/4 of the NE 1/4 for a distance of 1263.03 feet, more or less, to the point of beginning; being situated in Shelby County, Alabama.

05/19/1994-16236
01:24 PM CERTIFIED
SHELBY COUNTY JUDGE OF PROBATE
002 MCD 11.00