STATE OF ALABAMA TOWN OF INDIAN SPRINGS, VILLAGE

A RESOLUTION BY INDIAN SPRINGS VILLAGE, ALABAMA TO ADOPT A COMPREHENSIVE FLOOD DAMAGE AND CONTROL ORDINANCE TO ALLOW THE TOWN TO APPLY FOR AND PARTICIPATE IN THE NATIONAL FLOOD INSURANCE PROGRAM.

WHEREAS, certain areas of Indian Springs Village, Alabama are subject to periodic flooding, mudslides, mudflows, or flood-related erosion, causing serious damages to properties within these areas; and

WHEREAS, relief is available in the form of Federally subsidized flood insurance as authorized by the National Flood Insurance Act of 1968, as amended; and

WHEREAS, it is the intent of the Town of Indian Springs Village, through its Mayor and Town Council to require the recognition and evaluation of flood, mudslide, mudflow, or flood losses pursuant to 42 U.S.C Section 4001, et seq., as amended and other applicable Alabama Statutes as the same are Codified and Included in the Code of Alabama, 1975, as amended.

NOW, THEREFORE, BE IT ORDAINED by the Town Council of Indian Springs Village, Alabama, as Follows:

That the Town of Indian Springs Village, Alabama hereby:

- 1. Assures the Federal Insurance Administration that it will enact as necessary, and maintain in force for those areas having flood, mudslide, mudflow, or flood-related erosion hazards, adequate land use and control measures with effective enforcement provisions consistent with the Criteria set forth in 44 CFR, Part 60.3, as amended of the National Flood Insurance Program Regulations; and,
 - 2. Vests the Town Engineer with the responsibility, authority, and means to:
 - (a) Assist the Administrator, at his request, in his delineation of the limits of the area having special flood, mudslide, mudflow, or flood related erosion hazards; and,
 - (b) Provide such information as the Administrator may request concerning present uses and occupancy of the floodplain, mudslide, mudflow, or flood-related erosion areas; and,
 - (c) Cooperate with Federal, State, and local agencies and private firms which undertake to study, survey, map and identify floodplain, mudslide mudflow or flood related erosion areas, and cooperate with neighboring communities

04/26/1999-17451 11:27 AM CERTIFIED SHELBY COUNTY JUBGE OF PROBATE with respect to management of adjoining floodplain, mudslide, mudflow and/or flood related erosion areas to prevent aggravation of existing hazards; and,

- (e) Submit on the anniversary date of the community's initial eligibility, an annual report to the Administrator on the progress made during the past year within the community in the development and implementation of floodplain management measures; and,
- Upon occurrence, notify the Administrator in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce floodplain management regulations for a particular area. In order that all Flood Hazard Boundary Maps and Flood Insurance Rate Maps accurately represent the community's boundaries, include within such notification a copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished floodplain management regulatory authority.
- 3. Appoints the Town Engineer to maintain for public inspection and to furnish upon request, for the determination of applicable flood insurance risk premium rates within all areas having special flood hazards identified on a Flood Hazard Boundary Map or Flood Insurance Rate Map, any certificates of flood-proofing, and information on the elevation (in relation to mean sea level) of the level of the lowest habitable floor (including basement if habitable) of all new or substantially improved structures, and include whether or not such structures contain a basement; and if the structure has been flood-proofed, the elevation (in relation to mean sea level) to which the structure was flood proofed.
- 4. Agrees to take such other official action as may be reasonably necessary to carry out the objectives of the program.
 - 5. Agrees to apply the criteria, conditions and requirements stated herein as follows:

INDIAN SPRINGS VILLAGE, ALABAMA FLOOD DAMAGE PREVENTION ORDINANCE

(Non-Coastal Community)

ARTICLE 1

STATUTORY AUTHORIZATION, FINDINGS OF FACT PURPOSE AND OBJECTIVES

SECTION A. STATUTORY AUTHORIZATION

The Legislature of the State of Alabama has in Title 11, Chapter 19, Sections 1-24; Title 11, Chapter 45, Sections 1-11; Title 11, Chapter 52, Sections 1-84; and, Title 41, Chapter 9, Sections 163 and 166 of the Code of Alabama, 1975, as amended, authorized local government units to adopt regulations and ordinances designed to promote the public health, safety, and general welfare of its citizenry. Therefore, be it ordained by the Town of Indian Springs Village, Alabama through its Mayor and Town Council, as follows:

SECTION B. FINDINGS OF FACT

- (1) The flood hazard areas of the Town of Indian Springs Village, Alabama, are subject to periodic inundation which results in loss of life and property, health and safety hazards, disruption of commerce and governmental services, extraordinary public expenditures for flood relief and protection, and impairment of the tax base, all of which adversely affect the public health, safety and general welfare; and,
- These flood losses are caused by the occupancy in flood hazard areas of uses vulnerable to floods, which are inadequately elevated, flood-proofed, or otherwise unprotected from flood damages, and by the cumulative effect of obstructions in floodplains causes increases in flood heights and velocities.

SECTION C. STATEMENT OF PURPOSE

It is the purpose of this ordinance to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

require that uses vulnerable to floods, including facilities which serve such uses, be protected against flood damage at the time of initial construction; and,

- (2) restrict or prohibit uses which are dangerous to health, safety and property due to water or erosion hazards, or which increase flood heights, velocities, or erosion; and;
- (3) control filling, grading, dredging and other development which may increase flood damage or erosion, and;
- (4) prevent or regulate the construction of flood barriers which will unnaturally divert floodwaters or which may increase flood hazards to other lands; and,
- (5) control the alteration of natural floodplains, stream channels, and natural protective barriers which are involved in the accommodation of floodwaters.

SECTION D. OBJECTIVES

The objectives of this ordinance are:

- (1) to protect human life and health;
- (2) to minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, streets and bridges located in floodplains;
- (3) to help maintain a stable tax base by providing for the sound use and development of flood prone areas in such a manner as to minimize flood blight areas;
- (4) to minimize expenditure of public money for costly flood control projects;
- (5) to minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
- (6) to minimize prolonged business interruptions, and;
- (7) to insure that potential home buyers are notified that property is in a flood area.

ARTICLE 2

GENERAL PROVISIONS

SECTION A. LANDS TO WHICH THIS ORDINANCE APPLIES

This ordinance shall apply to all Areas of Special Flood Hazard within the jurisdiction of Indian Springs Village, Alabama.

SECTION B. BASIS FOR AREA OF SPECIAL FLOOD HAZARD

The Areas of Special Flood Hazard identified by the Federal Emergency Management Agency in its Flood Insurance Study (FIS), of Shelby County, Alabama, dated March 16, 1982, with accompanying maps and other supporting data and any revision thereto, are adopted by reference and declared a part of this ordinance. For those land areas acquired by a municipality through annexation, the current effective FIS and data for Shelby County are hereby adopted by reference. Areas of Special Flood Hazard may also include those areas known to have flooded historically or defined through standard engineering analysis by governmental agencies or private parties but not yet incorporated in a FIS.

SECTION C. ESTABLISHMENT OF DEVELOPMENT PERMIT

A Development Permit shall be required in conformance with the provisions of this ordinance PRIOR to the commencement of any Development activities.

SECTION D. COMPLIANCE

No structure or land shall hereafter be located, extended, converted or altered without full compliance with the terms of this ordinance and other applicable regulations.

SECTION E. ABROGATION AND GREATER RESTRICTIONS

This ordinance is not intended to repeal, abrogate, or impair any existing ordinance, easements, covenants, or deed restrictions. However, where this ordinance and another conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

SECTION F. INTERPRETATION

In the interpretation and application of this ordinance all provisions shall be: (1) considered as minimum requirements; (2) liberally construed in favor of the governing body, and; (3) deemed neither to limit nor repeal any other powers granted under state statutes or zoning ordinances or other regulations.

SECTION G. WARNING AND DISCLAIMER OF LIABILITY

The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur; flood heights may be increased by man-made or natural causes. This ordinance does not imply and shall not be construed to mean that land outside the Areas of Special Flood Hazard or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of Indian Springs Village, Alabama, or on any officer or employee thereof,

for any flood damages that result from reliance on this ordinance or any administrative decision lawfully made thereunder.

SECTION H. PENALTIES FOR VIOLATION

Violation of the provisions of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions shall constitute a misdemeanor. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than \$500.00 or imprisoned for not more than 10 days, or both, and in addition, shall pay all costs and expenses involved in the case. Each day such violation continues shall be considered a separate offense. Nothing herein contained shall prevent the Town of Indian Springs Village, Alabama from taking such other lawful actions as is necessary to prevent or remedy any violation.

ARTICLE 3

ADMINISTRATION

SECTION A. <u>DESIGNATION OF ORDINANCE ADMINISTRATOR</u>

The Town Engineer is hereby appointed to administer and implement the provisions of this ordinance.

SECTION B. PERMIT PROCEDURES

Application for a Development Permit shall be made to the Town Engineer on forms furnished by the Town of Indian Springs Village PRIOR to any development activities, and may include, but not be limited to, the following: plans in duplicate drawn to scale and showing the elevations of the area in question and the nature, location, dimensions, of existing or proposed structures, earthen fill placement, storage of materials or equipment, and drainage facilities.

Specifically, the following information is required:

- (1) Application Stage
 - (a) Elevation in relation to mean sea level (or highest adjacent grade) of the regulatory lowest floor level, including basement, of all proposed structures;
 - (b) Elevation in relation to mean sea level to which any non-residential structure will be flood proofed;

- (c) Design certification from a licensed professional engineer or architect that any proposed non-residential flood-proofed structure will meet the flood-reproofing criteria of Article 4, Sections B(2) and D(2);
- (d) Description of the extent to which any watercourse will be altered or relocated as a result of a proposed development, and;

(2) Construction Stage

- (a) For all new construction and substantial improvements, the permit holder shall provide to the Administrator an as-built certification of the regulatory floor elevation or flood-proofing level using appropriate FEMA elevation or flood-proofing certificate immediately after the lowest floor or flood-proofing is completed. When flood-proofing is utilized for non-residential structures, said certification shall be prepared by or under the direct supervision of a licensed professional engineer or architect and certified by same.
- (b) Any work undertaken prior to submission of these certifications shall be at the permit holder's risk. The town engineer shall review the above referenced certification data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to further progressive work being allowed to proceed. Failure to submit certification or failure to make said corrections required hereby, shall be cause to issue a stop-work order for the project.

SECTION C. <u>DUTIES AND RESPONSIBILITIES OF THE ADMINISTRATOR</u>

Duties of the Town Engineer shall include, but shall not be limited to:

- (1) Review all development permits to assure that the permit requirements of this ordinance have been satisfied.
- (2) Review proposed development to assure that all necessary permits have been received from governmental agencies from which approval is required by Federal or State law, including section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334, et seq., as amended. Require that copies of such permits be provided and maintained on file.
- (3) When Base Flood Elevation data or floodway data have not been provided in accordance with Article 2 Section B, then the Town Engineer shall obtain, review and reasonably utilize any base flood elevation and floodway data available from a Federal, State or other sources in order to administer the provisions of Article 4.

- (4) Verify and record the actual elevation in relation to mean sea level (or highest' adjacent grade) of the regulatory floor level, including basement, of all new construction or substantially improved structures in accordance with Article 3 (B(2).
- (5) Verify and record the actual elevation, in relation to mean sea level to which any new or substantially improved structures have been flood-proofed, in accordance with Article 4, Sections B (2) and D (2).
- (6) When flood-proofing is utilized for a structure, the Town Engineer shall obtain certification of design criteria from a licensed professional engineer or architect in accordance with Article 3(B)(1)(c) and Article 4(B)(2) or (D)(2).
- Notify adjacent communities and the Alabama Department of Natural Resources prior to any alteration or relocation of a watercourse and submit evidence of such notification to the Federal Emergency Management Agency (FEMA), and the Alabama Emergency Management Agency (AEMA).
- (8) For any altered or relocated watercourse, submit engineering data/analysis within six (6) months to the FEMA and State to ensure accuracy of community flood maps through the Letter of Map Revision process. Assure flood carrying capacity of any altered or relocated watercourse is maintained.
- (9) Where interpretation is needed as to the exact location of boundaries of the Areas of Special Flood Hazard (for example, where there appears to be a conflict between a mapped boundary and actual field conditions) the Town Engineer) shall make the necessary interpretation. Any person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this ordinance.
- (10) All records pertaining to the provisions of this ordinance shall be maintained in the office of the Town Engineer and shall be open for public inspection.

ARTICLE 4

PROVISIONS FOR FLOOD HAZARD REDUCTION

SECTION A. GENERAL STANDARDS

In ALL Areas of Special Flood Hazard the following provisions are required:

(1) New construction and substantial improvements of existing structures shall be anchored to prevent flotation, collapse or lateral movement of the structure;

- (2) New construction and substantial improvements of existing structures shall be constructed with materials and utility equipment resistant to flood damage;
- (3) New construction or substantial improvements of existing structures shall be constructed by methods and practices that minimize flood damage;
- (4) <u>Elevated Buildings</u>. All New construction or substantial improvements of existing structures that include ANY fully enclosed area located below the lowest floor formed by foundation and other exterior walls shall be designed so as to be an unfinished or flood resistant enclosure. The enclosure shall be designed to equalize hydrostatic flood forces on exterior walls by allowing for the automatic entry and exit of floodwater.
 - (a) Designs for complying with this requirement must either be certified by a licensed professional engineer or architect or meet the following minimum criteria:
 - (i) Provide a minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding;
 - (ii) The bottom of all openings shall be no higher than one foot above grade; and,
 - (iii) Openings may be equipped with screens, louvers, valves or other coverings or devices provided they permit the automatic flow of floodwater in both directions.
 - (b) So as not to violate the "Lowest Floor" criteria of this ordinance, the unfinished or flood resistant enclosure shall only be used for parking of vehicles, limited storage of maintenance equipment used in connection with the premises, or entry to the elevated area, and;
 - (c) The interior portion of such enclosed area shall not be partitioned or finished into separate rooms.
- (5) All heating and air conditioning equipment and components, all electrical, ventilation, plumbing, and other service facilities shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.

- Manufactured homes shall be anchored to prevent flotation, collapse, of lateral movement. Methods of anchoring may include, but are not limited to, use of overwhether top or frame ties to ground anchors. This standard shall be in addition to and consistent with applicable State requirements for resisting wind forces.
- (7) New and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system;
- (8) New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into the systems and discharges from the systems into floodwaters;
- (9) On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding, and;
- (10) Any alteration, repair, reconstruction or improvement to a structure which is not compliant with the provisions of this ordinance, shall be undertaken only if the nonconformity is not furthered, extended or replaced.

SECTION B. SPECIFIC STANDARDS

In ALL Areas of Special Flood Hazard designated as A1-30, AE, AH, A (with estimated BFE), the following provisions are required:

- (1) New construction and substantial improvements Where base flood elevation data are available, new construction or substantial improvement of any structure or manufactured home shall have the lowest floor, including basement, elevated no lower than two (2) feet above the base flood elevation. Should solid foundation perimeter walls be used to elevate a structure, openings sufficient to facilitate the unimpeded movements of floodwaters shall be provided in accordance with standards of Article 4, Section A(4), "Elevated Buildings".
- Non-Residential Construction New construction or the substantial improvement of any commercial, industrial, or non-residential structure shall have the lowest floor, including basement, elevated no lower than two (2) feet above the base flood elevation. Structures located in all A zones may be floodproofed in lieu of being elevated provided that all areas of the structure below the required elevation are watertight with walls substantially impermeable to the passage of water, and use structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effects of buoyancy. A licensed professional engineer or architect shall certify that the standards of this subsection are satisfied.
- (3) <u>Standards for Manufactured Homes and Recreational Vehicles</u> Where base flood elevation data are available:

- (a) All manufactured homes placed or substantially improved on: (i) individual, lots or parcels, (ii) in new or substantially improved manufactured home parks or subdivisions, (iii) in expansions to existing manufactured home parks or subdivisions, or (iv) on a site in an existing manufactured home park or subdivision where a manufactured-homehas incurred "substantial damage" as the result of a flood, must have the lowest floor including basement elevated no lower than two feet above the base flood elevation.
- (b) Manufactured homes placed or substantially improved in an existing manufactured home park or subdivision may be elevated so that either: (i) The lowest floor of the manufactured home is elevated no lower than two feet above the level of the base flood elevation, or (ii) The manufactured home chassis is elevated and supported by reinforced piers (or other foundation elements of at least an equivalent strength) of no less than 36 inches in height above grade.
- (c) All Manufactured homes must be securely anchored to an adequately anchored foundation system to resist flotation, collapse and lateral movement. (Refer to Article 4, Section A above)
- (d) All recreational vehicles placed on sites must either: (i) Be on the site for fewer than 180 consecutive days, fully licensed and ready for highway use if it is licensed, on it's wheels or jacking system, attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached structures or additions; or (ii) The recreational vehicle must meet all the requirements for "New Construction", including the anchoring and elevation requirements of Article 4 Section B (3) (a) (c), above.
- (4) Floodway- Located within Areas of Special Flood Hazard established in Article 2, Section B, are areas designated as floodways. A floodway may be an extremely hazardous area due to velocity floodwaters, debris or erosion potential. In addition, the area must remain free of encroachment in order to allow for the discharge of the base flood without increased flood heights.

Therefore, the following provisions shall apply:

Encroachments are prohibited, including earthen fill, new construction, substantial improvements or other development within the regulatory floodway. Development may be permitted however, provided it is demonstrated through hydro-logic and hydraulic analyses performed in accordance with standard engineering practice that the encroachment shall not result in any increase in flood levels or floodway widths during a base

flood discharge. A licensed professional engineer must provide supporting technical data and certification thereof.

(b) ONLY if Article 4 (B)(4)(a) above is satisfied, then any new construction or substantial improvement shall comply with all other applicable flood hazard reduction provisions of Article 4.

SECTION D. <u>BUILDING STANDARDS FOR STREAMS WITHOUT ESTABLISHED</u> BASE FLOOD ELEVATIONS AND/OR FLOODWAY (A-ZONES)

Located within the Areas of Special Flood Hazard (established in Article 2, Section B), where streams exist but no base flood data have been provided (A-Zones), OR where base flood data have been provided but a Floodway has not been delineated, the following provisions apply:

- (1) When base flood elevation data or floodway data have not been provided in accordance with Article 2(B), then the Town Engineer shall obtain, review, and reasonably utilize any scientific or historic Base Flood Elevation and floodway data available from a Federal, State, or other source, in order to administer the provisions of Article 4. ONLY if data are not available from these sources, then the following provisions (2 & 3) shall apply:
- (2) No encroachments, including structures or fill material, shall be located within an area equal to the width of the stream or twenty-five feet, whichever is greater, measured from the top of the stream bank, unless certification by a licensed professional engineer is provided demonstrating that such encroachment shall not result in any increase in flood levels during the occurrence of the base flood discharge.
- (3) In special flood hazard areas without base flood elevation data, new construction and substantial improvements of existing structures shall have the lowest floor of the lowest enclosed area (including basement) elevated no less than three (3) feet above the highest adjacent grade at the building site. Openings sufficient to facilitate the unimpeded movements of floodwaters shall be provided in accordance with standards of Article 4, Section A(4) "Elevated Buildings".

The Town Engineer shall certify the lowest floor elevation level and the record shall become a permanent part of the permit file.

SECTION E. STANDARDS FOR AREAS OF SHALLOW FLOODING (AO ZONES)

Areas of Special Flood Hazard established in Article 2, Section B, may include designated "AO" shallow flooding areas. These areas have base flood depths of one to three feet (1'-3') above ground, with no clearly defined channel. The following provisions apply:

(1) All new construction and substantial improvements of residential and non-residential structures shall have the lowest floor, including basement, elevated to the flood depth number specified on the Flood Insurance Rate Map (FIRM) above the highest adjacent grade. If no flood depth number is specified, the lowest floor, including basement, shall be elevated at least three feet (3) above the highest adjacent grade. Openings sufficient to facilitate the unimpeded movements of floodwaters shall be provided in accordance with standards of Article 4, Section A(4), "Elevated Buildings".

The Town Engineer shall certify the lowest floor elevation level and the record shall become a permanent part of the permit file.

- (2) New construction or the substantial improvement of a non-residential structure may be flood-proofed in lieu of elevation. The structure, together with attendant utility and sanitary facilities, must be designed to be water tight to the specified FIRM flood level plus two (2) feet above highest adjacent grade, with walls substantially impermeable to the passage of water, and structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A licensed professional engineer or architect shall certify that the design and methods of construction are in accordance with accepted standards of practice for meeting the provisions above, and shall provide such certification to the official as set forth above and as required in Articles 3(B)(1)(c) and (3) (B) (2).
- (3) Drainage paths shall be provided to guide floodwater around and away from any proposed structure.

SECTION F. STANDARDS FOR SUBDIVISIONS

- (1) Base flood elevation data shall be provided for subdivision proposals and all other proposed development, including manufactured home parks and subdivisions, greater than fifty (50) lots or five (5) acres, whichever is less.
 - (2) All subdivision proposals shall be consistent with the need to minimize flood damage;
- (3) All subdivision proposals shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize flood damage; and,
- (4) All subdivision proposals shall have adequate drainage provided to reduce exposure to flood hazards.

ARTICLE 5

VARIANCE PROCEDURES

SECTION A. GENERAL STANDARDS

- (1) The Board of Zoning Adjustment of Indian Springs Village, Alabama as established by Town of Indian Springs Village, Alabama, shall hear and decide requests for appeals or variance from the requirements of this ordinance.
- (2) The board shall hear and decide appeals when it is alleged an error in any requirement, decision, or determination is made by the Town Engineer in the enforcement or administration of this ordinance.
- (3) Any person aggrieved by the decision of the Board of Zoning Adjustment of Indian Springs Village, Alabama may appeal such decision within fifteen (15) days to the Circuit Court Of Shelby County, pursuant to Section 11-52-81 of the Code of Alabama, 1975, as amended.
- (4) Variances may be issued for the repair or rehabilitation of Historic Structures upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as an Historic structure and the variance is the minimum to preserve the historic character and design of the structure.
- (5) Variances may be issued for development necessary for the conduct of a functionally dependent use, provided the criteria of this Article are met, no reasonable alternative exists, and the development is protected by methods that minimize flood damage during the base flood and additional threats to public safety.
- (6) Variances shall not be issued within any designated floodway if ANY increase in flood levels during the base flood discharge would result.
- (7) In reviewing such requests, the Board of Zoning Adjustment of Indian Springs Village, Alabama, shall consider all technical evaluations, relevant factors, and all standards specified in this and other sections of this ordinance.

SECTION B. <u>CONDITIONS FOR VARIANCES</u>:

- (1) A variance shall be issued **ONLY** when there is:
 - (a) a finding of good and sufficient cause,
 - (b) a determination that failure to grant the variance would result in exceptional hardship, and;

- (c) a determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
- (2) The provisions of this ordinance are minimum standards for flood loss reduction, therefore any deviation from the standards must be weighed carefully. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief; and, in the instance of an Historic Structure, a determination that the variance is the minimum necessary so as not to destroy the historic character and design of the building.
- (3) Any applicant to whom a variance is granted shall be given written notice specifying the difference between the base flood elevation and the elevation of the proposed lowest floor and stating that the Cost of flood insurance will be commensurate with the increased risk to life and property resulting from the reduced lowest floor elevation.
- (4) The Town Engineer shall maintain the records of all appeal actions and report any variances to the Federal and State Emergency Management Agencies upon request.
- (5) Upon consideration of the factors listed above and the purposes of this ordinance, the Board of Zoning Adjustment of Indian Springs Village may attach such conditions to the granting of variances as it deems necessary to further the purposes of this ordinance.

ARTICLE 6

DEFINITIONS

Unless specifically defined below, words or phrases used in this ordinance shall be interpreted so as to give them the meaning they have in common usage and to give this ordinance its most reasonable application.

- "Addition to an existing building" means any walled and roofed expansion to the perimeter of a building in which the addition is connected by a common load-bearing wall other than a fire wall. Any walled and roofed addition which is connected by a fire wall or is separated by an independent perimeter load-bearing wall shall be considered "New Construction".
- "Appeal" means a request for a review of the Town Engineer's interpretation of any provision of this ordinance.
- "Area of shallow flooding" means a designated AO or AH Zone on a community's Flood Insurance Rate Map (FIRM) with base flood depths from one to three feet, and/or where a clearly

defined channel does not exist, where the path of flooding is unpredictable and indeterminate, and where velocity flow may be evident.

"Area of special flood hazard" is the land in the floodplain within a community subject to a one percent or greater chance of flooding in any given year. In the absence of official designation by the Federal Emergency Management Agency, Areas of Special Flood Hazard shall be those designated by the local community and referenced in Article 2, Section B.

"Base flood" means the flood having a one percent chance of being equaled or exceeded in any given year.

"Basement" means that portion of a building having its floor sub-grade (below ground level) on all sides.

"Breakaway wall" means a wall that is not part of the structural support of the building and is intended through its design and construction to collapse under specific lateral loading forces, without causing damage to the elevated portion of the building or the supporting foundation system.

"Building" means any structure built for support, shelter, or enclosure for any occupancy or storage.

"Development" means any man-made change to improved or unimproved real estate, including, but not limited to, buildings or other structures, mining, dredging, filling, grading, paving, excavation, drilling operations, and permanent storage of equipment or materials.

"Elevated building" means a non-basement building built to have the lowest floor of the lowest enclosed area elevated above the ground level by means of fill, solid foundation perimeter walls, pilings, columns, piers, or shear walls adequately anchored so as not to impair the structural integrity of the building during a base flood event.

"Existing Construction" means any structure for which the "start of construction" commenced before the effective date of this Ordinance which is the FIRST-floodplain management code or ordinance adopted by the Town of Indian Springs Village, Alabama, as a basis for its participation in the National Flood Insurance Program (NFIP)].

"Existing manufactured home park or subdivision" means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum the installation of utilities, the construction of streets, and final site grading or the pouring of concrete pads) is completed before the effective date of this Ordinance which is the FIRST-floodplain management code or ordinance adopted by the Town of Indian Springs Village, Alabama, as a basis for its participation in the National Flood Insurance Program (NFIP)].

"Expansion to an existing manufactured home park or subdivision" means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed, including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads.

"Flood" or "flooding" means a general and temporary condition of partial or complete inundation of normally dry land areas from:

- (a) the overflow of inland or tidal waters; or
- (b) the unusual and rapid accumulation or runoff of surface waters from any source.

"Flood Hazard Boundary Map (FHBM)" means an official map of a community, issued by the Federal Insurance Administration, where the boundaries of areas of special flood hazard have been designated as Zone A.

"Flood Insurance Rate Map (FIRM)" means an official map of a community, issued by the Federal Insurance Administration, delineating the areas of special flood hazard and/or risk premium zones applicable to the community.

"Flood Insurance Study" the official report by the Federal Insurance Administration evaluating flood hazards and containing flood profiles, and water surface elevations of the base flood.

"Floodplain" means any land area susceptible to flooding.

"Floodway" (Regulatory Floodway) means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height.

"<u>Functionally dependent facility</u>" means a facility which cannot be used for its intended purpose unless it is located or carried out in close proximity to water, such as a docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, or ship repair facilities. The term does not include long-term storage, manufacture, sales, or service facilities.

"Highest adjacent grade" means the highest natural elevation of the ground surface, prior to construction, adjacent to the proposed walls of a structure.

"Historic Structure" means any structure that is;

(a) Listed individually in the National Register of Historic Places (a listing maintained by the U.S. Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register:

- (b) Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district:
- (c) Individually listed on a state inventory of historic places and determined as eligible by states with historic preservation programs which have been approved by the Secretary of the Interior; or
- (d) Individually listed on a local inventory of historic places and determined as eligible by communities with historic preservation programs that have been certified either:
 - (1) By an approved state program as determined by the Secretary of the Interior, or
 - (2) Directly by the Secretary of the Interior in states without approved programs.

"Levee" means a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding.

"Levee System" means a flood protection system which consists of a levee, or levees, and associated structures, such as closure and drainage devices, which are constructed and operated in accordance with sound engineering practices.

"Lowest floor" means the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, used solely for parking of vehicles, building access, or storage, in an area other than a basement, is not considered a building's lowest floor, provided that such enclosure is not built so as to render the structure in violation of other provisions of this code.

"Mangrove stand" means an assemblage of mangrove trees which is mostly low trees noted for a copious development of interlacing adventitious roots above the ground and which contain one or more of the following species: Black mangrove (Avicennia Nitida); red mangrove (Rhizophora Mangle); white mangrove (Languncularia Racemosa) and buttonwood (Conocarpus Erecta).

"Manufactured home" means a building, transportable one or more sections, built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term also includes park trailers, travel trailers, and similar transportable structures placed on a site for 180 consecutive days or longer and intended to be improved property.

"Mean Sea Level" means the average height of the sea for all stages of the tide. It is used as a reference for establishing various elevations within the floodplain. For purposes of this

ordinance, the term is synonymous with National Geodetic Vertical Datum (NGVD) of 1929 or other datum.

"National Geodetic Vertical Datum (NGVD)" as corrected in 1929 is a vertical control used as a reference for establishing varying elevations within the floodplain.

"New construction" means ANY structure (see definition) for which the "start of construction" commenced after the effective date of this Ordinance which is the FIRST-floodplain management code or ordinance adopted by the Town of Indian Springs Village, Alabama, as a basis for its participation in the National Flood Insurance Program (NFIP), and includes any subsequent improvements to the structures.

"New manufactured home park or subdivision" means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after the effective date of this Ordinance which is the FIRST-floodplain management code or ordinance adopted by the Town of Indian Springs Village, Alabama, as a basis for its participation in the National Flood Insurance Program (NFIP).

"Repetitive Loss" means flood-related damages sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25 percent of the market value of the structure before the damages occurred.

"Recreational vehicle" means a vehicle which is:

- (1) Built on a single chassis;
- (2) 400 square feet or less when measured at the largest horizontal projection;
- (3) Designed to be self-propelled or permanently towable by a light duty truck; and
- (4) Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

"Start of construction" means the date the development permit was issued, provided the actual start of construction, repair, reconstruction, or improvement was within 180 days of the permit date. The actual start means the first placement of permanent construction of the structure such as the pouring of slabs or footings, installation of piles, construction of columns, or any work beyond the stage of excavation, and includes the placement of a manufactured home on a foundation. Permanent construction does not include initial land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation

for a basement, footings, piers or foundations or the erection of temporary forms; nor does it include the installation on the property of buildings appurtenant to the permitted structure, such as garages or sheds not occupied as dwelling units or part of the main structure. (NOTE: accessory structures are NOT exempt from any ordinance requirements) For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

"Structure" means a walled and roofed building that is principally above ground, a manufactured home, a gas or liquid storage tank.

"Substantial damage" means damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred. Substantial damage also means flood-related damages sustained by a structure on two separate occasions during a 10-year period for which the cost of repairs at the time of each such flood event, on the average, equals or exceeds 25 percent of the market value of the structure before the damages occurred.

"Substantial improvement" means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before the "start of construction" of the improvement. This term includes structures which have incurred "repetitive loss" or "substantial damage", regardless of the actual repair work performed. The market value of the building should be (1) the appraised value of the structure prior to the start of the initial repair or improvement, or (2) in the case of damage, the value of the structure prior to the damage occurring. This term includes structures which have incurred "substantial damage", regardless of the actual amount of repair work performed.

For the purposes of this definition, "substantial improvement" is considered to occur when the first alteration of any wall, ceiling, floor, or other structural part of the building commences, whether or not that alteration affects the external dimensions of the building. The term does not, however, include either: (1) Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions or; (2) Any alteration of a "historic structure", provided that the alteration will not preclude the structure's continued designation as a "historic structure".

"Substantially improved existing manufactured home parks or subdivisions" is where the repair, reconstruction, rehabilitation or improvement of the streets, utilities and pads equals or exceeds 50 percent of the value of the streets, utilities and pads before the repair, reconstruction or improvement commenced.

"Town Engineer" shall mean the duly designated Engineer of the Town of Indian Springs Village, Alabama, including either a self-employed contract engineer or town employee.

"Variance" is a grant of relief from the requirements of this ordinance which permits construction in a manner otherwise prohibited by this ordinance.

ARTICLE 7

SEVERABILITY

If any section, clause, sentence, or phrase of this Ordinance is held to be invalid or unconstitutional by any court of competent jurisdiction, then said holding shall in no way effect the validity of the remaining portions of this Ordinance.

ARTICLE 8

EFFECTIVE DATE

These Flood Control Regulations shall take effect and be in force from and after the date of their adoption and publication as required by law..

ORDAINED, ADOPTED AND APPROVED, this the day of _____

1

Upon Recommendation by the Planning Commission for the Town of Indian Springs Village, Alabama

By : ≤

Gerald A. Templeton, Chairman

Mayor and Governing Body:

Gene Weingarten, Mayor

Herb Robins, Council Member

Patricia Crapet, Council Member

Stewart Dudley, Council Member

Gary Dennis Council Member

Arthur Johnson, Qouncil Member

CERTIFICATION

Indian Springs Town Hall 2635 Cahaba Valley Road Indian Springs, AL

Town Clerk's Office 88 Indian Crest Drive Indian Springs, AL

North Shelby Fire District No. 2 Caldwell Mill Road Indian Springs, AL

Sunny Food Store No. 8 Caldwell Mill Road Indian Springs, AL

Paul J. Stephens

Town Clerk

Indian Springs Village, Alabama

Inst # 1999-17451